





ROLLSTAND CONFIGURATIONS

- 1 to 2 Roll Stands
- Zero Speed Splicer
- Flying Paste Splicer

CONFIGURATION OPTIONS

- Wireless Laser Bar Code Scanner
- Calculate Wrap Weight
- Sample and Hold Wrap Weight
- Calculate Core Weight
- Sample and Hold Core Weight
- Excess Strip Waste Event Op Code Event Trigger
- Reject Roll Event Op Code Trigger
- Minimum Roll Weight for Return to Inventory
- Auto-Print Return to Stock Roll Label
- Auto-Print Reject Stock Roll Label
- Auto-Cycle Shift Based on Day of Week/Press

WASTE SCALE

- Lamp Post Hook Scale
- Floor Scale
- Bench Scale
- Can use most commercially available load cell platforms, consult Overbridge for detail.

DATABASE

- Resident MSDE
- Native connectivity for Microsoft SQL Server, Sybase, or Oracle

OPERATING SYSTEM

- Windows 2KPro or XP Pro

PHYSICAL DIMENSIONS

- Weight: 110 Lbs. Width 37" Depth 22"
- Floor Mount Pedestal Enclosure

ELECTRICAL

- Main: 15A 120V AC
- Control Inputs: 10 - 24V DC Opto-Isolated